

EvoTouch



LC
LongLifeCell

10K
10.000Hours


Low weight


Connectivity


Temperature

IP65
Box


Consumption

Clorador salino con display táctil

- Célula bipolar de alta eficiencia
- Funciones domóticas avanzadas
- Detección automática de cubierta
- Display táctil TFT color. Intuitivo y fácil de usar gracias a su interfaz gráfica
- Control y monitorización remota a través del entorno EYPOOLS

Compact salt water chlorinator with touch screen

- High Efficiency Bipolar cell
- Advanced domotic functions
- Automatic cover detection
- TFT colour touch screen, easy to use
- Control all the pool settings using the integrated EYPOOLS

	EVoTOUCH15	EVoTOUCH20	EVoTOUCH25	EVoTOUCH35
Tensión de alimentación Power Supply	230Vac – 110Vac – 50/60Hz			
Corriente máxima de la célula Max cell current	3,75A	5A	6,25A	8,75A
Producción gr/hora Gr/hour production	15gr/h	20gr/h	25gr/h	35gr/h
Potencia máxima Max Power	80,25W	107W	133,75W	187,25W
Tensión máxima de la célula Max cell voltage	21,4V	21,4V	21,4V	21,4V
Sal necesaria Salt required	4gr/l			
Selección de idioma Language selection	✓	✓	✓	✓
Regulación de cloro manual Manual regulation of chlorine	✓	✓	✓	✓
Regulación de cloro automático Automatic regulation of chlorine	✓	✓	✓	✓
Indicación de lectura redox Indicator of ORP Values	✓	✓	✓	✓
Indicación de lectura pH Indicator of pH Values	✓	✓	✓	✓
Indicación falta de sal Automatic indicator of lack of salt	✓	✓	✓	✓
Indicación exceso de sal Automatic indicator of salt excess	✓	✓	✓	✓
Indicación T° del agua Indicator of water temperature	✓	✓	✓	✓
Autolimpiable Self-cleaning	✓	✓	✓	✓
Indicador lectura de sal Salt level indicator	✓	✓	✓	✓
Indicador estado vida célula Cell life indicator	✓	✓	✓	✓
Relé programable(1) Programmable relay	✓	✓	✓	✓
Contador de horas de funcionamiento Working hours counte	✓	✓	✓	✓
DESCONEXIONES AUTOMÁTICAS AUTOMATIC ALARMS				
Falta de flujo de agua Caused by lack of water flow	✓	✓	✓	✓
Acumulación de gas en la célula Caused by gas accumulation in the cell	✓	✓	✓	✓
Por cortocircuito Caused by overload	✓	✓	✓	✓
Por circuito abierto Caused by Short circuit	✓	✓	✓	✓
Por sobre temperatura Caused by over temperature	✓	✓	✓	✓
OPCIONES OPTIONS				
Kit Advanced (ORP) Kit Advanced (ORP)	✓	✓	✓	✓
Kit Auto (pH) Kit Auto (pH)	✓	✓	✓	✓
Kit sonda temperatura Temperature probe Kit	✓	✓	✓	✓
Kit PRO CL Kit PRO CL	✓	✓	✓	✓
Kit Sonda Agua Water sensor kit	✓	✓	✓	✓
Kit Conductivity Water sensor Kit	✓	✓	✓	✓
Kit Connect (Eypools) Kit connect (Eypools)	Opcional / Optional			
MEDIDAS MEASUREMENTS				
Equipo Machine	250 x 308 x 89 mm			
Embalaje Packaging	460 x 430 x 220 6 kg			